ORDERING WORK-READY TRUCKS IS EASIER THAN EVER!



Palfinger American Roll-off is pleased to announce a partnership with Fontaine Modification Company to install Cable Hoist Roll-off bodies in 4 configurations with 3 tarp options. This makes ordering a high-quality, work-ready truck for your customer dramatically easier! Fontaine provides chassis ordering assistance, installs the body and manages the logistics from the truck plant to the drive away company. Contact Fontaine to get started!

MODEL	CAPACITY	MAX.	CONTAINS	RLENGTH OPERATI	NG PRESSL	RE LEAR CAICT	NO TARP	
ARB 75-22	75,000 lbs.	22'	48	3,000 PSI	176"	186"	18,000/46,000	
ARB 75-24	75,000 lbs.	24'	48	3,000 PSI	194"	204"	18,000/46,000	
ART 75-22	75,000 lbs.	22'	48	4,500 PSI	176"	186"	18,000/46,000	
ART 75-24	75,000 lbs.	24'	48	4,500 PSI	194"	204"	18,000/46,000	

WARRANTY

→ Three years on all structural components, one year on hydraulic components

STANDARD FEATURES

- → Composite Fenders
- → Heavy Duty 3 Hole Bumper with LED Lighting
- → 36x18x18" Heavy Duty Steel Toolbox
- → Heavy Duty Ratchet Binders

OPTIONS

- → PALFINGER/Roll Rite Hydraulic Tarper with Aluminum or Steel Arms
- → Pioneer Rack & Pinion RP 4500 SARG autotarper kit
- → Short Stops; Customer to Specify Location
- → 20k Non Steer/Steerable Lift Axle
- → 13k Steerable lift Axle









REQUIRED CHASSIS ITEMS

- → Clean Back of Cab Package
- → 22' System, 176" C/T NO TARP, 186" C/T With Tarp
- → 24' System, 194" C/T NO TARP, 204" C/T With Tarp
- → Minimum 2,500,000 in. lbs. RBM Frame
- → Fontaine Ship Through

RECOMMENDED CHASSIS ITEMS

- → 18,000lb min. front axle
- → 46,000lb min rear axles



0	R	D	Ε	R	F	0	R	N	V	

1. SYS1	ГЕМ							
/	ARB 75,000lb	ART 75,000lb						
2. SYS1	TEM SIZE							
2	22' System	24' System						
3. TRAI	NSMISSION							
[Eaton Autoshift	Eaton Manual	Allison					
4. TARF	PER							
F	Roll Rite/Palfinger Hydraulic (Aluminum or Steel Arms)							
F	Roll Rite DC400 with Remote, Aluminum Arms							
F	Pioneer Rack & Pinion RP4500 SARG							
	RT STOP DIMENSIONS asure from front stops, mouth to n	nouth.)						
	inches.							
6. LIFT	AXLES							
2	20k Non Steer	20k Steer	13k Steer, QTY*:					
7. DEAI	LER INFORMATION		*More than 1 requires a 24' System.					
Dealer (aler Code: Chassis Order # or VIN #:							





Dealer

Representative: ___

Signature: